

VOYAGER PART NUMBER

VY

SIDE

LORR

SHELL
COLOR

C,B,T,ORJ

EN

SIZE

21-30

FIRMNESS
CATEGORY

D

1-5

(L) Left, (R) Right

(C) Caucasian, (B) Brown,
(T) Tan, (J) Jet Black

128g
LIGHTER



College Park designs and manufactures a full line of anatomically correct, custom built prosthetic solutions. College Park is ISO 13485 certified with an extensive focus on quality testing, and proudly sources and produces all products entirely in the USA. With precise engineering and quality manufacturing, College Park is committed to innovating human locomotion solutions for users all over the world.



The Voyager was designed to achieve ultimate comfort and rotation for any journey. With vertical shock absorption, responsive springs, and built-in torsion, this high-performance foot can feel more natural to the user. With a newly reduced weight and superior range of motion, this foot accommodates a wide range of activities. The sleek Voyager uses a hybrid material approach—blending flexible Intelliweave® composites with durable carbon fiber to maximize function.


VERTICAL SHOCK

Comfort is key. The Voyager allows for up to 10mm of vertical shock absorption, which can reduce impact and pressure on the body. Its vertical compliance does not affect function during normal use.



MATERIAL FUSION

The Voyager's design embraces the best of both worlds. The upper spring is composed of College Park's Intelliweave composite technology. These fibers are woven by hand in a 3D pattern for flexibility and strength. The carbon fiber base spring enhances function by providing a dynamic response and increased energy return.



ROTATE ON YOUR OWN AXIS

Made of titanium and stainless steel, the Voyager's adjustable, built-in unit offers a maximum of 20° of internal *and* external rotation. Users can twist with ease, which may improve comfort for walking or high-impact sports. This smooth movement can help reduce forces to a patient's socket and residual limb. With simple adjustments using a 4mm hex key, the Voyager's unique torsion feature offers additional, integrated energy return.



TECHNICAL SPECIFICATIONS

FOOT BASE

Intelliweave® + Carbon Fiber

MOUNTING

Endo

SIZES

21-30 cm

WEIGHT LIMIT

21-25 cm	275 lbs (125kg)
26-30 cm	330 lbs (150 kg)

BUILD HEIGHT

7.5 in (19.1 cm)

WEIGHT*

1,174 g

128g
LIGHTER!

WARRANTY

3 years

L CODES**

L5987, L5984

PDAC
APPROVED!

IMPACT LEVEL



ENVIROSHIELD†



*26 cm model, including pyramid and Enviroshell. **The listing of codes with these products should not be construed as a guarantee for coverage or payment. Ultimate responsibility for the coding of services/products rests with the individual practitioner.

†Caucasian, Tan, Brown or Jet Black.

